

Ergonomic Series Nozzles

Maximum comfort for demanding washdown operations.




Standard and low-flow models are available to support water conservation programs.

Sani-Lav ergonomic nozzles are designed to reduce operator fatigue while delivering powerful washdown performance. The balanced ergonomic grip, lightweight design, and trigger control allow operators to clean longer with less strain while maintaining superior cleaning power.

Why the ergonomic series nozzles stand out

- Durable stainless steel body and components for long service life
- Ergonomic grip reduces operator fatigue during extended washdown
- Balanced lightweight design for improved control
- Reinforced nylon cover for comfort and protection
- Low-flow models available to reduce water consumption



Ergonomic Series Nozzles

Universal Features									
Model	Color	Inlet	Material	Max PSI	Max TEMP	GPM @ 100 PSI	Weight	Includes	
NP1	Safety Orange	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	7.9	1.6	3/4" Swivel Hose Barb	
NP1B	Black	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	7.9	1.6	3/4" Swivel Hose Barb	
NP1W	White	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	7.9	1.6	3/4" Swivel Hose Barb	
NP1R	Red	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	7.9	1.6	3/4" Swivel Hose Barb	
NP1X	Safety Orange	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	7.9	1.6	-	
NP1BX	Black	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	7.9	1.6	-	
NP1WX	White	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	7.9	1.6	-	
NP1RX	Red	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	7.9	1.6	-	
NP10	Safety Orange	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	Low flow 4.9	1.6	3/4" Swivel Hose Barb	
NP1B0	Black	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	Low flow 4.9	1.6	3/4" Swivel Hose Barb	
NP1W0	White	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	Low flow 4.9	1.6	3/4" Swivel Hose Barb	
NP1R0	Red	3/4" GHT	Stainless, Reinforced Nylon	150	200°F/93°C	Low flow 4.9	1.6	3/4" Swivel Hose Barb	

Water Flow Rate Comparison			
PSI	Standard GPM	Low-flow GPM	Water Saving %
20	3.2	2.0	38%
30	4.1	2.5	39%
40	4.8	2.9	40%
50	5.4	3.3	39%
60	6.0	3.6	40%
70	6.4	3.9	39%
80	7.1	4.3	39%
90	7.4	4.5	39%
100	7.9	4.9	38%
110	8.2	5.0	39%
120	8.6	5.4	37%
130	9.0	5.6	38%
140	9.3	5.7	39%
150	9.9	6.1	38%

Additional Features

- Heavy-duty Stainless Steel body and stainless steel components
- Insulated cover with yellow arrow directions
- Stainless steel handle
- Safety shut off trigger when released
- Replacement parts available
- Dimensions: L 5.91" x H 6.97"
- Swivel hose adapter (included with models NP1, NP1B, NP1W, NP1R, NP10, NP1B0, NP1W0, NP1R0)



Replacement Parts	
Description	Model
Orange Insulated Cover	A NP1C
Black Insulated Cover	B NP1BC
White Insulated Cover	C NP1WC
Red Insulated Cover	D NP1RC



Model N20S Swivel Hose Barb

.75" GHT Female

