

Large Industrial Nozzles – Brass Series

Engineered for maximum cleaning power.



Sani-Lav large industrial nozzles are engineered for demanding sanitation environments in food processing and industrial facilities. A heavy-duty brass body combined with stainless steel internal components provides exceptional strength, durability, and long service life under continuous daily washdown use.

Why choose the large brass nozzles

- Heavy-duty brass construction – built for long service life in demanding washdown environments
- Standard and low-flow models available – supports water conservation and sustainability programs
- Insulated impact-resistant cover – protects hands from heat while improving grip and comfort
- Instant shut-off trigger – helps reduce water waste and improve operator safety
- Serviceable design – replacement parts available to extend product life and reduce downtime



Large Industrial Nozzles – Brass Series

Universal Features									
Model	Color	Inlet	Material	Max PSI	Max Temp.	GPM @ 100 PSI	Weight	Includes	
N8	Safety Orange	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	7.3	2.3 lbs.	—	
N8B	Black	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	7.3	2.3 lbs.	—	
N8W	White	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	7.3	2.3 lbs.	—	
N8R	Red	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	7.3	2.3 lbs.	—	
N820	Safety Orange	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	7.3	2.3 lbs.	3/4" Swivel Hose Barb	
N8B20	Black	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	7.3	2.3 lbs.	3/4" Swivel Hose Barb	
N8W20	White	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	7.3	2.3 lbs.	3/4" Swivel Hose Barb	
N8R20	Red	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	7.3	2.3 lbs.	3/4" Swivel Hose Barb	
N81	Safety Orange	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	Low Flow 3.3	2.3 lbs.	—	
N81B	Black	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	Low Flow 3.3	2.3 lbs.	—	
N81W	White	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	Low Flow 3.3	2.3 lbs.	—	
N81R	Red	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	Low Flow 3.3	2.3 lbs.	—	
N8120	Safety Orange	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	Low Flow 3.3	2.3 lbs.	3/4" Swivel Hose Barb	
N81B20	Black	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	Low Flow 3.3	2.3 lbs.	3/4" Swivel Hose Barb	
N81W20	White	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	Low Flow 3.3	2.3 lbs.	3/4" Swivel Hose Barb	
N81R20	Red	3/4" GHT	Brass, EPDM Cover	150	200°F/93°C	Low Flow 3.3	2.3 lbs.	3/4" Swivel Hose Barb	

Water Flow Rate Comparison			
PSI	Standard GPM	Low-flow GPM	Water Saving %
20	3.1	1.4	55%
30	3.8	1.8	53%
40	4.5	2.0	56%
50	5.1	2.3	55%
60	5.5	2.5	55%
70	6.0	2.7	55%
80	6.4	3.0	53%
90	6.9	3.1	55%
100	7.3	3.3	55%
110	7.7	3.5	55%
120	8.0	3.7	54%
130	8.4	3.8	55%
140	8.7	3.9	55%
150	9.2	4.2	54%



Additional Features

- Heavy-duty brass body and brass and stainless steel components
- Insulated rubber cover with yellow arrow directions
- Stainless steel handle
- Safety shut off trigger when released
- Replacement parts available
- Dimensions: L 6.25" x H 6.25"
- Swivel hose barb (included with models N820, N8B20, N8W20, N8R20, N8120, N81B20, N81W20, N81R20)

