

Mid-Sized Industrial Nozzles – Aluminum Series

Lightweight performance with optional low-flow water savings.



Low-flow models reduce water usage over 20%

Sani-Lav mid-sized industrial nozzles are engineered for daily use in food processing, beverage production, and industrial sanitation environments. Durable metal construction, ergonomic handling, and serviceable components provide reliable washdown performance and long service life.

Why choose the aluminum series nozzles

- Aluminum body with stainless steel components for maximum corrosion resistance
- Ideal for harsh sanitation and chemical environments
- Long service life in food processing applications
- Resists rust, chemicals, and high temperature washdowns
- Replacement parts available



Mid-Sized Industrial Nozzles – Aluminum Series

Universal Features								
Model	Color	Inlet	Material	Max PSI	Max Temp.	GPM @ 100 PSI	Weight	Includes
N1A	Safety Orange	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	5.0	1.0 lbs.	—
N1AB	Black	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	5.0	1.0 lbs.	—
N1AW	White	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	5.0	1.0 lbs.	—
N1AY	Yellow	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	5.0	1.0 lbs.	—
N1AR	Red	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	5.0	1.0 lbs.	—
N1AX	Safety Orange	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	Low Flow 3.3	1.0 lbs.	—
N1ABX	Black	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	Low Flow 3.3	1.0 lbs.	—
N1AWX	White	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	Low Flow 3.3	1.0 lbs.	—
N1AYX	Yellow	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	Low Flow 3.3	1.0 lbs.	—
N1ARX	Red	3/4" GHT	Aluminum, EPDM Cover	150	200°F/93°C	Low Flow 3.3	1.0 lbs.	—

Water Flow Rate Comparison			
PSI	Standard GPM	Low-flow GPM	Water Saving %
20	2.1	1.4	33%
30	2.6	1.8	31%
40	3.0	2.0	33%
50	3.5	2.1	40%
60	3.8	2.4	37%
70	4.1	2.7	34%
80	4.3	3.0	30%
90	4.8	3.2	33%
100	5.0	3.3	34%
110	5.3	3.6	32%
120	5.5	3.7	33%
130	5.7	3.9	32%
140	6.0	4.1	32%
150	6.3	4.3	32%

Additional Features

- Heavy-duty aluminum body and brass and stainless steel components
- Insulated rubber cover with yellow arrow directions
- Stainless steel handle
- Safety shut off trigger when released
- Replacement parts available
- Dimensions: L 5.25" x H 5"
- Swivel hose adapter (sold separately)



Model
N1AB
N1ABX



Model
N1AW
N1AWX



Model
N1AY
N1AYX



Model
N1AR
N1ARX

Variable Spray Nozzle – trigger lever controls variable spray pattern.

