

Small Industrial Nozzles

Standard and low-flow models are available to support water conservation programs.



Model
N2
N2X

Model
N2G
N2GX

Model
N2BL
N2BLX

Model
N2B
N2BX

Low-flow models reduce water usage over 20%

Sani-Lav industrial spray nozzles are engineered for daily use in food processing and industrial sanitation environments. Durable metal construction, ergonomic handling, and optional low-flow models help facilities reduce water consumption while maintaining effective washdown performance.

Why our small nozzles stand out

- Durable metal construction – stronger than plastic-bodied alternatives
- Standard and low-flow models available – supports sustainability and water conservation programs
- Color options available – helps prevent cross-contamination in food facilities
- Designed for industrial sanitation environments



Small Industrial Nozzles

Universal Features								
Model	Color	Inlet	Material	Max PSI	Max Temp.	GPM @ 100 PSI	Weight	Includes
N2	Safety Orange	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	10.9	0.5 lbs.	3/4" GHT Threaded Tip
N2B	Black	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	10.9	0.5 lbs.	3/4" GHT Threaded Tip
N2W	White	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	10.9	0.5 lbs.	3/4" GHT Threaded Tip
N2R	Red	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	10.9	0.5 lbs.	3/4" GHT Threaded Tip
N2BL	Blue	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	10.9	0.5 lbs.	3/4" GHT Threaded Tip
N2G	Green	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	10.9	0.5 lbs.	3/4" GHT Threaded Tip
N2Y	Yellow	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	10.9	0.5 lbs.	3/4" GHT Threaded Tip
N2X	Safety Orange	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	Low Flow 7.9	0.5 lbs.	3/4" GHT Threaded Tip
N2BX	Black	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	Low Flow 7.9	0.5 lbs.	3/4" GHT Threaded Tip
N2WX	White	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	Low Flow 7.9	0.5 lbs.	3/4" GHT Threaded Tip
N2RX	Red	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	Low Flow 7.9	0.5 lbs.	3/4" GHT Threaded Tip
N2BLX	Blue	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	Low Flow 7.9	0.5 lbs.	3/4" GHT Threaded Tip
N2GX	Green	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	Low Flow 7.9	0.5 lbs.	3/4" GHT Threaded Tip
N2YX	Yellow	3/4" GHT	Zinc, Santoprene Cover	100	150°F/67°C	Low Flow 7.9	0.5 lbs.	3/4" GHT Threaded Tip

Water Flow Rate Comparison			
PSI	Standard GPM	Low-flow GPM	Water Saving %
20	4.7	3.3	30%
30	5.7	4.2	26%
40	6.4	4.9	23%
50	7.4	5.5	26%
60	8.0	6.0	25%
70	8.9	6.4	28%
80	9.6	7.1	26%
90	10.2	7.5	26%
100	10.9	7.9	28%

- Additional Features**
- Heavy-duty zinc body and brass and stainless steel components
 - Insulated rubber cover
 - Hardened temperature resistant plastic handle
 - Safety shut off trigger when released
 - Dimensions: L 3.5" x H 5"
 - Hose Adapter (sold separately)

